

MICRO SERIES

# AIMPOINT® MICRO H-2 WITH MOUNT FOR TIKKA T3



## AIMPOINT® MICRO H-2 WITH MOUNT FOR TIKKA T3

Item No.	200221
Aiming dot size	2 MOA
Battery type	3V lithium battery, type CR2032.
Battery life - Day time use	50 000h (over 5 years of continuous use)

## OVERVIEW

Aimpoint® Micro H-2 with integrated Tikka T3 low mount.

The Aimpoint® Micro H-2 2MOA and Tikka T3 low mount are sold as a set with Art. No. 200221. The mount is also sold **separately**, Art. No. 200225

*Launched 2015.*

## AIMPOINT® MICRO H-2 MOUNT FOR TIKKA T3

The Tikka T3 low rail mount has been developed according to requests from dog handlers, who desire a robust low mount for Aimpoint® Micro and Tikka T3. The mount slides on from behind and is secured by 6 mounting screws to keep in in place. This mount makes it as low as you possibly can go. The two attachment points lead to a solid and professional mount for the most demanding hunters.

## AIMPOINT® MICRO H-2

The extremely compact Micro H-2 offers up to five years of constant on power from a single CR-2032 battery, and has 12 brightness settings for optimal performance in any light conditions. This sight is completely waterproof, and is a result of feedback coming from hard core customers desiring an even more hard core Micro sight. With a redesigned and reinforced house body, as well as flip-up covers protecting the lenses, the Micro H-2 can withstand all types of environmental conditions. And thanks to new optical lenses and cutting edge lens coatings, the optical performance and the shape and clarity of the red dot are radically improved.

# AIMPOINT® MICRO H-2 WITH MOUNT FOR TIKKA T3

## TECHNICAL SPECIFICATIONS

GENERAL SPECIFICATIONS	POWER SOURCE	ENVIRONMENTAL SPECIFICATIONS
Item No.: 200221	Battery type: 3V lithium battery, type CR2032.	Temperature range operation: -30°C to +60°C (-20°F to +140°F)
OPTICAL SPECIFICATIONS	Battery life - Day time use: 50 000h (over 5 years of continuous use)	Temperature range storage: -51°C to +71°C (-60°F to +160°F)
Operating principle: Reflex collimator sight with LED	Power intensity: 1 Off position and 12 daylight settings	Submersible: To a depth of 5 m (15 ft.)
Optical magnification: 1x	PHYSICAL SPECIFICATIONS	
Aiming dot size: 2 MOA	Length sight only: 68 mm (2.7 in)	
Dot intensity: Visible against a background luminance of 0.1 to 55 000 lx	Length conf: 126 mm (4.94 in)	
Dot color: Peak Wavelength: 655 ± 15 nm	Width sight only: 27 mm (1.1 in)	
NVD compatible: No	Height sight only: 36 mm (1.4 in)	
Optical coating: Anti-reflex, all surfaces and multi-layer.	Height conf: 41 mm (1.6 in)	
Clear aperture: 18 mm (.71 in)	Weight sight only (incl battery): 94 g, (3.3 oz)	
Eye relief: Unlimited	Weight conf: 150 g (5.3 oz) incl mount	
	Housing material: High strength Aluminum	
	Housing finish and color: Semi-matte black	
	Material mount and spacer std conf: High strength Aluminum	
	Surface treatment: Anodized, semi matte	
	Adjustment: Range ±1 m at 100 meters (±1 yds at 100 yds) in windage and elevation, 1 click = 13 mm at 100 meters = 10 mm at 80 meters = .44 in at 100 yds	